

## Required information for RVU in COMMISSION REGULATION (EU) No. 1254/2014 ANNEX IV

(a)	Supplier's name	MITSUBISHI ELECTRIC	
(b)	Model name	VL-100U5-E	VL-100EU5-E
		※Out of scope(No.1253/2014)	
(c)	SEC (kWh/(m2.a))	Cold region: -61.2 Average region: -28.8	
(d)	Declared typology	RVU,BVU	
(e)	Type of drive	-	
(f)	Type of HRS	Recuperative	
(g)	Thermal efficiency (%)	73	
(h)	Maximum flow rate (m3/h)	100	
(i)	Electric power input (kW)	0.03	
(j)	Casing sound power level (dB)	52	
(k)	Reference flow rate (m3/s)	0.03	
(l)	Reference pressure difference (Pa)	10	
(m)	SPI (W/(m3/h))	0.30	
(n)	Control factor and typology	Manual control	
(o)	Maximum leakage rate (%)	-	
(p)	Mixing rate of non-ducted	-	
(q)	Visual filter warning	Refer to instruction book	
(r)	Instructions to install regulated supply/exhaust grilles for unidirectional ventilation	-	
(s)	Internet address for disassembly instructions	<a href="http://erp.mitsubishielectric.eu/">http://erp.mitsubishielectric.eu/</a>	
(t)	Airflow sensitivity for non-ducted units	-	
(u)	air tightness for non-ducted units	-	
(v)	AEC (kWh/a)	Average region 4.6	
(w)	AHS (kWh primary energy/a)	Average 39.5 Cold 77.4 Warm 17.9	

### MITSUBISHI ELECTRIC CORPORATION

Manufactured by: MITSUBISHI ELECTRIC CORPORATION

TOKYO BLDG., 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN

Importer in EU: MITSUBISHI ELECTRIC EUROPE B.V.

HARMAN HOUSE, 1 GEORGE STREET, UXBRIDGE, MIDDLESEX, UB8 1QQ, U.K.



**ENERG** Y IJA  
енергия · ενέργεια IE IA



VL-100U5-E/VL-100EU5-E



52  
dB

100 m<sup>3</sup>/h

ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI  
2016 1254/2014

357PP0304